

Digitale Messuhr SYLVAC SYSTEM IP67

Digital indicator SYLVAC SYSTEM IP67



AUSFÜHRUNG

- Robuster Aufbau
- Wasser- und kühlmittelfest
- Schutzart IP67 nach IEC 60529 mit u. ohne Datenkabel
- Zoll/metrisch, Preset, Nullstellung
- Schaft Durchmesser 8 mm

MIT DATENAUSGANG

- Sparmodus und automatisches Wiedereinschalten (SIS), absolute System
- Display drehbar über 270°
- Personalisierbare Taste für wählbare Funktion

STANDARD ZUBEHÖR

- Batterie
- Bedienungsanleitung, Garantieschein, Prüfschein

FEATURES

- Robust construction
- Water and coolant resistant
- Protection rating IP67 according to IEC 60529 even connected with cable
- Inch/Metric, Preset, zero setting
- Ø8mm stem diameter

WITH DATA OUTPUT

- Automatic wake-up and sleeping mode (S.I.S system), absolute System
- rotating display over 270°
- New technology with configurable menus

STANDARD ACCESSORIES

- Battery
- Warranty card, instruction manual, test certificate

TECHNISCHE DATEN / SPECIFICATIONS

Messbereich	Auflösung	Genauigkeit	A	B	C	Bestell-Nr.
Range	Resolution	Accuracy	mm	mm	mm	Code No.
Dial Work Serie						
0-12.5mm	0.01mm	±0.02mm	123	19	20.5	408-95-0
0-25mm	0.01mm	±0.02mm	149	19	33	408-01-0
0-50mm	0.01mm	±0.02mm	264	19	58	408-02-0
0-100mm	0.01mm	±0.02mm	447	19	108	408-04-0
0-150mm	0.01mm	±0.03mm	574	19	158	408-06-0
0-12.5mm	0.001mm	±0.004mm	123	19	20.5	408-95-4
0-25mm	0.001mm	±0.005mm	149	19	33	408-01-4
0-50mm	0.001mm	±0.007mm	264	19	58	408-02-4
0-100mm	0.001mm	±0.008mm	417	19	108	408-04-4
0-150mm	0.001mm	±0.015mm	574	19	158	408-06-4

Abmessung / Dimension

