

Allround platform scale with a wide range of communication options, verification optional - also available as high-resolution version with fine display



1 Verification plug, for verified balances this enables you to separate the display device and platform without affecting the verification, e.g. for installing the scale in a packing and dispatch table, pit frame etc. at a later date. Please order this at the same time as you purchase your scale, see *accessories*



Practical Flip/Flop display device: flexible positioning e.g. free-standing or screwed to the wall (optional). By rotating the upper housing shell you can determine the angle of the display as well as the cable outlet. Factory Option for an additional cost, delivery time + 2 working days, KERN KIB-M01, see *Accessories* on the right, please indicate when placing your order

Features

- A wide range of (optional) data interfaces allows easy transfer of weighing data to tablets, laptops, PCs, networks, smartphones, printers, etc.
- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers. Only possible through data interface RS-232, other interfaces on request., for details see page 19
- Standardised, simplified concept of operation
- Thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Platform: weighing plate of stainless steel, painted steel base, silicone-coated aluminium load cell with protection against dust and water splashes IP65
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard, to give the most accurate weighing result

Technical data

- Large LCD display, digit height 25 mm
- Weighing platform dimensions W×D×H, stainless steel

A	300×240×110 mm	B	300×300×110 mm
C	400×300×110 mm	D	500×400×120 mm
E	650×500×150 mm	F	800×600×200 mm

- Dimensions of display device W×D×H 268×115×80 mm
- Cable length of display device approx. 3 m
- Permissible ambient temperature -10 °C/40 °C


Accessories

- Protective working cover, scope of delivery 5 items, KERN EOC-A01S05
- Stand, to be screwed onto the platform, height of stand approx. 330 mm, KERN EOC-A05
- Mount to fasten the display device to the platform, KERN EOC-A03
- Benchtop stand incl. wall mount for display device, KERN EOC-A04
- Internal rechargeable battery pack, operating time up to 26 h with backlight, charging time approx. 3 h, KERN KFB-A01
- USB data interface, for transferring weighing to the PC, printer etc., must be ordered at purchase, KERN KIB-A03
- Bluetooth data interface for wireless data transfer to PC or tablets, must be ordered at purchase, KERN KIB-A04
- WiFi interface for wireless connection of the balance to networks and WiFi capable devices, such as tablets, laptops or smartphones, continuous data transfer, must be ordered at purchase, KERN KIB-A10

- Ethernet data interface, to connect an IP-based Ethernet network, continuous data transfer, must be ordered at purchase, KERN KIB-A02
- Signal lamp, including interface, for visual support of weighing with tolerance range, must be ordered at purchase, KERN KIB-A06
- 1** Verification plug, for verified balances this enables you to separate the display device and platform without affecting the verification, e.g. for installing the scale in a packing and dispatch table, pit frame etc. at a later date. Please order this at the same time as you purchase your scale, KERN KIB-A12
- 2** Alibi memory, for paperless archiving of the weighing results with ID no., gross/net/tare value, date and time, must be ordered at purchase, KERN KIB-A13
- Alibi memory, including USB interface for exporting weighing results to external data storage media, such as, for example, USB sticks, hard drives, etc., must be ordered at purchase, KERN KIB-A01
- Modification of the display device, to move the cable outlet to the front of the display device, ideal e.g. for subsequent wall installation of the display device (standard configuration ex works: rear outlet), Factory Option, delivery time + 2 working days, KERN KIB-M01

3 Note: In addition to the RS-232 data interface, which is integrated as standard, only one other data interface can be installed and operated


STANDARD




OPTION



FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Net weight approx. kg	Weighing plate	Options	
							Verification	DAkkS Calibr. Certificate
							 KERN	DAkkS KERN
Multi-range balance with high-resolution display, with increasing load it switches automatically to the next largest weighing range [Max] and readout [d] and when the load is fully removed, the balance switches back to the lower range								
IOC 6K-4*	3 6	0,1 0,2	-	20 40	6	B	-	963-128
IOC 10K-4*	6 15	0,2 0,5	-	40 100	6	A	-	963-128
IOC 10K-4L*	6 15	0,2 0,5	-	40 100	8	C	-	963-128
IOC 30K-4*	15 30	0,5 1	-	100 200	8	C	-	963-128
IOC 60K-3*	30 60	1 2	-	200 400	8	C	-	963-129
IOC 60K-3L*	30 60	1 2	-	200 400	12	D	-	963-129
IOC 100K-3*	60 150	2 5	-	400 1000	12	D	-	963-129
IOC 100K-3L*	60 150	2 5	-	400 1000	22	E	-	963-129
IOC 300K-3*	150 300	5 10	-	1000 2000	22	E	-	963-129
IOC 600K-2*	300 600	10 20	-	2000 4000	32	F	-	963-130
Multi-range balance without high-resolution display								
IOC 6K-3M*	3 6	1 2	1 2	20 40	6	B	965-228	963-128
IOC 10K-3M*	6 15	2 5	2 5	40 100	6	A	965-228	963-128
IOC 10K-3LM*	6 15	2 5	2 5	40 100	8	C	965-228	963-128
IOC 30K-3M*	15 30	5 10	5 10	100 200	8	C	965-228	963-128
IOC 60K-2M*	30 60	10 20	10 20	200 400	8	C	965-229	963-129
IOC 60K-2LM*	30 60	10 20	10 20	200 400	12	D	965-229	963-129
IOC 100K-2M*	60 150	20 50	20 50	400 1000	12	D	965-229	963-129
IOC 100K-2LM*	60 150	20 50	20 50	400 1000	22	E	965-229	963-129
IOC 300K-2M*	150 300	50 100	50 100	1000 2000	22	E	965-229	963-129
IOC 600K-1M*	300 600	100 200	100 200	2000 4000	32	F	965-230	963-130

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

- 2** It is essential that a verified balance which transfers measurements to external devices using an interface, has an alibi memory (KIB-A13). It is not possible to upgrade later

1 * ONLY WHILE STOCKS LAST