



ODC-87, ODC-88



Eyepiece camera fixed into the tube

**Features**

- With the KERN eyepiece cameras you can convert your standard microscope to a digital microscope, by replacing one eyepiece of your non-digital microscope with an eyepiece camera and connect this to your computer via USB
- The universal eyepiece can be connected to the microscope as well as to a laptop or PC using the USB cable (2.0 or 3.0, see table)
- The power supply is through the USB cable, which means that no additional power supply is required
- Your daily work is made significantly easier with the very best synchronisation, a high frame rate as well as stable image performance together with our software

- As well as the camera, the delivery includes a USB cable (length: 1,5 m), two eyepiece adapters and an object micrometer to calibrate the software
- Possible tube diameters:  
23,2 mm (Standard)  
30,0 mm (Eyepiece adapter)  
30,5 mm (Eyepiece adapter)

STANDARD



Model	Resolution	Interface	FPS	Sensor	Sensor size	Colour/ Monochrome	Supported operating system
<b>KERN</b>							
ODC 874	3 MP	USB 2.0	3 – 7,5	CMOS	1/2,7"	colour	Win XP, Vista, 7, 8, 10
ODC 881	5 MP	USB 3.0	15 – 30	CMOS	1/2,5"	colour	Win XP, Vista, 7, 8, 10

USB Microscope – USB 2.0 KERN ODC-89

**The digital USB microscope for rapid testing or for hobby use**



ODC 895

**Features**

- The USB hand-held microscope is designed for rapid and simple observations. Ideally suited for coins, plants, insects and skin samples for all hobby scientists, children and students
- With the USB microscope you can easily adjust the magnification to suit all conventional samples. The zoom range can be adjusted to a magnification of 10× as well as 200×
- The eight LEDs fitted in the ring shape ensure strong and effective illumination of your sample. Use the adjustment wheel on the cable to control the illumination setting
- Cable length: 1,4 m

**Stand with focus wheel:**

- Work area: 150×80 mm
- Focus range: 60 mm
- Overall dimensions: 150×80×135 mm

STANDARD



Model	Resolution	Interface	FPS	Sensor	Sensor size	Supported operating system	Magnification levels	Focusing stand	Illumination
<b>KERN</b>									
ODC 895	2 MP	USB 2.0	15 – 30	CMOS	1/3,2"	Win XP, Vista, 7, 8, 10	10×, 200×	Focus wheel	8× LED