

Counting scale KERN CIB



Robust counting scale with large article memory, convenient operating philosophy and checkweighing display, counting resolution up to 30,000 points

Features

- Innovative counting with tolerance range (Checkweighing): The counting process can be supported visually and/or audibly and this therefore makes portion division, dispensing and grading easier
 - visual signal: the colour of the display changes depending on the counting result (not enough/ok/too much)
 - audible signal: the frequency of the audible signal changes depending on the counting result (not enough/ok/too much), can be switched off
- Ideal for workshops for people with disabilities, particularly loud or quiet environments, where operators change frequently, etc.
- Three displays for weight display, reference weight, total pieces
- Precise counting: The automatic reference weight optimisation of reference weight gradually improves the average piece weight value

- Programmable using numerical key pad:
 - required reference quantity
 - known reference weight
- Counting results memory: adds up all individual piece counts, result is shown in total weight and total pieces
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- 20 direct price keys for frequently recurring reference weights and PRE-Tare values
- Memory for 50 reference weights and PRE-Tare values
- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (kitchen, sales office, cafeteria, Food industry-Laboratory etc.)
- Two balances in one: Changes from counting mode to weighing mode at the touch of a key
- Energy management: Backlight turns off after 5 sec, can be switched off
- Protective working cover included with delivery


Technical data

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, WxD 315x215 mm
- Overall dimensions WxDxH, 350x330x120 mm
- Net weight approx. 3,6 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN RIB-A01S05
- Internal rechargeable battery pack, operating time up to 160 h without backlight, charging time approx. 14 h, KERN GAB-A04

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Smallest part weight [Normal] g/ piece	Counting resolution Points	Option
					DAKkS Calibr. Certificate DAKkS KERN
KERN CIB 3K-4	3	0,2	1	30.000	963-127
KERN CIB 6K-4	6	0,5	2	30.000	963-128
KERN CIB 10K-3	15	1	5	30.000	963-128
KERN CIB 30K-3	30	2	10	30.000	963-128

- 
Internal adjusting:
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)
- 
Adjusting program CAL:
 For quick setting up of the balance's accuracy. External adjusting weight required
- 
Easy Touch:
 Suitable for the connection, data transmission and control through PC or tablet.
- 
Memory:
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.
- 
Alibi memory:
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.
- 
KERN Universal Port (KUP):
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WLAN, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
- 
Data interface RS-232:
 To connect the balance to a printer, PC or network
- 
RS-485 data interface:
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible
- 
USB data interface:
 To connect the balance to a printer, PC or other peripherals
- 
Bluetooth* data interface:
 To transfer data from the balance to a printer, PC or other peripherals
- 
WiFi data interface:
 To transfer data from the balance to a printer, PC or other peripherals
- 
Control outputs (optocoupler, digital I/O):
 To connect relays, signal lamps, valves, etc.
- 
Analogue interface:
 to connect a suitable peripheral device for analogue processing of the measurements
- 
Interface for second balance:
 For direct connection of a second balance
- 
Network interface:
 For connecting the scale to an Ethernet network
- 
KERN Communication Protocol (KCP):
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
- 
GLP/ISO log:
 The balance displays weight, date and time, independent of a printer connection
- 
GLP/ISO log:
 With weight, date and time. Only with KERN printers.
- 
Piece counting:
 Reference quantities selectable. Display can be switched from piece to weight
- 
Recipe level A:
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out
- 
Recipe level B:
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display
- 
Totalising level A:
 The weights of similar items can be added together and the total can be printed out
- 
Percentage determination:
 Determining the deviation in % from the target value (100 %)
- 
Weighing units:
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details
- 
Weighing with tolerance range:
 (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model
- 
Hold function:
 (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value
- 
Protection against dust and water splashes IPxx:
 The type of protection is shown in the pictogram.
- 
Suspended weighing:
 Load support with hook on the underside of the balance
- 
Battery operation:
 Ready for battery operation. The battery type is specified for each device
- 
Rechargeable battery pack:
 Rechargeable set
- 
Universal plug-in power supply:
 with universal input and optional input socket adapters for
 A) EU, CH, GB
 B) EU, CH, GB, USA
 C) EU, CH, GB, USA, AUS
- 
Plug-in power supply:
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
- 
Integrated power supply unit:
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
- 
Weighing principle: Strain gauges
 Electrical resistor on an elastic deforming body
- 
Weighing principle: Tuning fork
 A resonating body is electromagnetically excited, causing it to oscillate
- 
Weighing principle: Electromagnetic force compensation
 Coil inside a permanent magnet. For the most accurate weighings
- 
Weighing principle: Single cell technology:
 Advanced version of the force compensation principle with the highest level of precision
- 
Verification possible:
 The time required for verification is specified in the pictogram
- 
DAkkS calibration possible (DKD):
 The time required for DAkkS calibration is shown in days in the pictogram
- 
Factory calibration (ISO):
 The time required for Factory calibration is shown in days in the pictogram
- 
Package shipment:
 The time required for internal shipping preparations is shown in days in the pictogram
- 
Pallet shipment:
 The time required for internal shipping preparations is shown in days in the pictogram

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.