Micromar 40 EWRi-S

Digital micrometer

FUNCTIONS

- RESET (set display to zero)
- ABS (display can be set to zero without losing reference to ORIGIN)
- mm/inch
- ORIGIN (for entering a numerical value)
- LOCK function (key lock)
- TOL (Tolerance and Warning Limits Input)
- HOLD (storage of measured values)
- DATA (data transmission)
- Bidirectional data interface (external output and input option of characteristic values as well as setting of individual lock functions by MarCom Software)

FEATURES

- With blade-type measuring surfaces
- High contrast digital display
- Stainless spindle is hardened ٠ throughout and ground
- Quick drive • Sliding spindle
- Ratchet is integrated in the • thimble
- Lacquered steel frame, heat insulated
- Software: MarCom Professional free download: www.mahr.com/ marcom (only for Mahr data cables and wireless systems with USB and RS-232 interface)
- Digit height: 10 mm
- Data interface: Integrated ٠ Wireless
- Energy supply: Battery life ٠ approx. 2 years
- Battery type: CR 2032 (3V Lithium)
- IP protection category: IP 65
- Package contains: instruction • manual, battery, setting standard (measuring range of 25-50 mm), case



20085

 $((\bullet))$

ABS

#ID

REF

system

 \bigcirc

IP 65

Application:

• For measuring recesses, grooves, etc.

TECHNICAL DATA

Order no.	Туре	Mea- suring range	Mea- suring range	Mea- suring surface	Resolution	Error limit	Spindle thread pitch	Mea- suring force	Standard	Model contact surface
		mm	inch		mm/inch	μm	mm	Ν		
4157141	40 EWRi-S	0 –25	0 -1 "	hardened steel	0.001 / .00005"	4	5	5 –10	DIN 863-3	Blade
4157142	40 EWRi-S	25 –50	1 –2″	hardened steel	0.001 / .00005″	4	5	5 –10	DIN 863-3	Blade
4157143	40 EWRi-S	50 –75	2 –3″	hardened steel	0.001 / .00005"	5	5	5 –10	DIN 863-3	Blade
4157144	40 EWRi-S	75 –100	3 –4″	hardened steel	0.001 / .00005″	5	5	5 –10	DIN 863-3	Blade

Order no.	а	b	С	
	mm	mm	mm	
4157141	32	11.5	57	
4157142	44	13.5	82	
4157143	57	15.5	107	
4157144	73	17	132.5	

25

ACCESSORIES

Order no.	der no. Description	
4102220	Receiver for instruments with Integrated Wireless	i-Stick
4158000	Stand for holding outside micrometers	41 H



Micromar | Micrometers



i-Stick

