## **ABSOLUTE Borematic**

## **ABSOLUTE Borematic Complete Unit Sets**

This is a Three-Point Digimatic Snap Open Bore Gauge Set with a display unit for each measuring head.

It offers you the following benefits:

- It enables you to take measurements easily and quickly.
- Titanium-coated measuring pins gives you excellent durability and impact resistance.
- 330° rotatable display unit also gives you easy reading at any angle.
- GO/NG tolerance judgement function.



568-959

Metric					
No.	Range [mm]	Individual ranges	Digital step	Setting rings included	Mass [g]
568-9	<b>55</b> 6 - 12	6-8 mm 8-10 mm 10-12 mm	0,001 mm	Ø8 mm (177-125) Ø10 mm (177-126)	1450
568-9	<b>56</b> 12 - 25	12-16 mm 16-20 mm 20-25 mm	0,001 mm	Ø16 mm (177-177) Ø20 mm (177-286)	1520
568-9	<b>57</b> 25 - 50	25-30 mm 30-40 mm 40-50 mm	0,001 mm	Ø30 mm (177-288) Ø40 mm (177-290)	1750
568-9	<b>58</b> 50 - 75	50-63 mm 62-75 mm	0,001 mm	Ø62 mm (177-314)	1490
568-9	<b>59</b> 75 - 100	75-88 mm 87-100 mm	0,001 mm	Ø87 mm (177-318)	1610





Functions	ABSOLUTE Borematic Complete Unit Sets
ON/OFF	0
ZERO/ABS	<b>a</b>
Function lock	0
DATA (output with cable) /	<b>a</b>
HOLD (display value)	
2 x PRESET	0
Data output	<b>a</b>
GO/±NG judgement	0

Specifications		
Display	LCD, character height: 11 mm	
Measuring pins	Titanium coated tungsten carbide (6 - 12 mm) Titanium coated hardened steel (12 - 125 mm)	
Power supply	1 battery SR-44	
Battery life	approx. 5.000 hours	
Delivered	Including box, key, battery, setting ring, certificate of inspection (instruments only - certificate of inspection for setting rings not included).	

## Optional accessories

No.	Description	
905338	Digimatic Cable, Flat Straight Type, 1m	
905409	Digimatic Cable, Flat Straight Type, 2m	
06AFM380F	USB Input Tool Direct (Digimatic USB), Digi/Digi2, Flat Straight Type	
02AZD880G	U-WAVE-T, Buzzer Type, Wireless Transmitter	
02AZD730G	U-WAVE-T, IP67 Type, Wireless Transmitter	
02AZD790F	AZD790F U-WAVE-T Connection Cable F, Flat Straight Type	
952322	Holtest, Borematic Extension 100mm, 6-12mm	
952621	Holtest, Borematic Extension 150mm, 12-20mm	
952622	Holtest, Borematic Extension 150mm, 20-50mm	
952623	Holtest, Borematic Extension 150mm, 50-300mm	

## Consumable spares

No.	Description
938882	Battery SR44 1.5V



Titanium coated measuring surfaces for durability

