Functions	Series 50			
ORIGIN (ABS-Zero)	<b>a</b>			
ON/OFF	<b>a</b>			
Low voltage alarm	•			
Data output	<b>(4)</b>			

## Specifications

Max. response speed	Unlimited
Display	LCD, Character Height 10 mm
Battery life	Approx. 20000 hours under normal use

#### **Optional accessories**

No.	Description			
959149	Digimatic Cable, Straight, Data Button,, 1m			
959150	Digimatic Cable, Straight, Data Button,, 2m			
06AFM380C	USB Input Tool Direct (Digimatic USB), Digi/Digi2, Straight, with Data Button			
02AZD880G	U-WAVE-T, Buzzer Type, Wireless Transmitter			
02AZD730G	U-WAVE-T, IP67 Type, Wireless Transmitter			
02AZD790C	U-WAVE-T Connection Cable C, Straight, with Data Button			
959143	Data Hold Unit			

## Consumable spares

No.	Description
938882	Battery SR44 1.5V

# **ABSOLUTE Digimatic Calipers for Long Range**

Series 500 ABSOLUTE

This digimatic caliper allows you to take reliable measurements and offers you the following benefits:

- It has a robust design (6 x 25 mm beam) for large measuring ranges.
- ABSOLUTE System delivers reliable measurements.
- The slider provides smooth, stable and comfortable operation.
- Character height: 10 mm



500-500-10

#### Metric

No.	Range [mm]	Accuracy	Data output	Resolution	Mass [g]	L [mm]	A [mm]	B [mm]	C [mm]	D [mm]	H [mm]
500-500-10	0 - 450	±0,05 mm	Yes	0,01mm	1170	630	38	47	35,9	90	25
500-501-10	0 - 600	±0,05 mm	Yes	0,01mm	1350	780	38	47	35,9	90	25
500-502-10	0 - 1.000	±0,07 mm	Yes	0,01mm	3300	1.240	50	60	49,8	130	32



