

Specifications

Power supply	AC-Adapter, 10 V 120 mA or 5 V from the USB
Timer function	1 s-99 h 59 min 59 s (100 h)
Dimensions (WxDxH)	55 x 58 x 31 mm
Timer tolerance	±8 s/24 h
Mass	84 g



Sample application with DMX Box

Digimatic Timerbox

Series 63

This timerbox allows you to connect to the footswitch connector of a Mitutoyo interface to trigger data transfer, based on a time interval.

- It can be used with all Mitutoyo interfaces featuring 3,5mm TRS Foot switch connectors (Mono) such as USB Input Tool Direct. It works as a time-controlled footswitch.



63AAA107



Sample application with USB Input Tool Direct

No.
63AAA107

Digimatic Switch Box


Series 63/939

This switch box is a distribution box that connects 3-5 Digimatic tools to one channel interface (for example a DMX-1 USB).

Optional accessories

No.	Description
936937	Digimatic Cable, Flat 10-Pin Type, 1m
965014	Digimatic Cable, Flat 10-Pin Type, 2m
937179T	Footswitch for SPC

937179T for 63AAA030 only



1: cable 936937 (1 m), 965014 (2 m)



63AAA030



939039

No.	Data output	Data input	Footswitch connector
63AAA030	1 x Digimatic (1 channel)	5 x Digimatic	Yes
939039	1 x Digimatic (1 channel)	3 x Digimatic	No

Digimatic Tolerance Box

Series 011

It allows you to connect Digimatic measuring instruments for visual -NG/GO/+NG evaluations.

Specifications

Power supply	AC-Adapter or 2 batteries LR6 (AA)
Dimensions (WxDxH)	117 x 73 x 24 mm

Optional accessories

No.	Description
011037	Battery, LR6, 1,5V, 4 pcs.



011516

No.	Remarks
011516	Tolerance setting with the measuring instrument