Digimatic Screw Thread Micrometers with Interchangeable Tips

Series 326

This Digimatic Screw Thread Micrometer should be used with optional, interchangeable, anvils/spindle-tips that allow you to measure a wide range of metric/unified and Whitworth screw-thread pitch diameters.





A metric (unified) 60° setting standard is included with all models except those measuring range from 0-25 mm.







Interchangeable anvils/spindle tips in matching pairs

Metric

No.	Range [mm]	Spindle feed error	Digital step	Measuring force [N]	Mass [g]	A [mm]	B [mm]
326-251-30	0 - 25	3 µm	0,001 mm	5-10	350	39,5	25
326-252-30	25 - 50	3 µm	0,001 mm	5-10	380	64,5	32
326-253-30	50 - 75	3 µm	0,001 mm	5-10	470	90	45
326-254-30	75 - 100	3 um	0.001 mm	5-10	510	115,6	65







Functions	Series 326
ZERO/ABS	•
Auto Power OFF	a
after 20 min. non use	
Low voltage alarm	•
Function lock	a
HOLD	•
2 x PRESET	a

Specifications

Display	LCD, character height 7,5 mm
Measuring face	Interchangeable anvil/ spindle inserts (optional)
Measuring spindle	With spindle lock, ø 6,35 mm, spindle pitch 0,5 mm
Scale	Thimble and sleeve satin chrome finish
Power supply	1 battery SR-44
Battery life	Approx. 2,4 years
Delivered	Including box, key, 1 battery, setting standard (from 25 mm upward) interchangeable tips are optional

Standard accessories

No.	Description
167-261	Setting Standard Screw Thread Micrometer, 60°, Length: 25mm
167-262	Setting Standard Screw Thread Micrometer, 60°, Length: 50mm
167-263	Setting Standard Screw Thread Micrometer, 60°, Length: 75mm

Optional accessories

optional accessories	
No.	Description
05CZA662	Digimatic Cable with Data Button IP Type, 1m, Micrometer Type
05CZA663	Digimatic Cable with Data Button IP Type, 2m, Micrometer Type
06AFM380B	USB Input Tool Direct (Digimatic USB), Digi/Digi2, With Data Button IP Micrometer Type
264-622	U-WAVE fit, IP67 Type, Wireless Transmitter for Micrometer
264-623	U-WAVE fit, Buzzer Type, Wireless Transmitter for Micrometer
02AZF310	Connection Unit, U-WAVE fit, Waterproof Type

Consumable spares

No.	Description
938882	Battery SR44 1.5V

