

Compact Roundness Measurement **ROUNDTTEST RA-120/120P**

Catalog No. E15008(2)



Compact roundness tester equipped with a wide range of analysis features and capable of flexibly accommodating a variety of workpieces

Mitutoyo

Roundtest RA-120

- Best-in-class rotational accuracy in compact type roundness measuring instruments
- Fine adjustment on both X- and Z-axes
- Multiple analyses through simple operation
- D.A.T. function *except for centering/leveling device: Analog head type
- Scaled Z-axis
- Continuous ID and OD measurement
- High-precision air bearing
- Wide-range detector
- Straightforward setup and display of results
- Built-in printer
- Supports 16 languages



Simple, interactive display screen


The large LCD screen with backlight shows easy-to-understand measurement results and graphs. Forms can be checked and notch processing can be set while observing the displayed graphs.

Measurement screen

- Set the position of the detector and measurement conditions here
- During measurement, graphs are displayed in real time




▲ Measurement screen



▲ Measurement in progress screen

Measurement results

- Filter, display magnification, etc., can be altered
- Besides circles, development views can also be displayed



Result screen ▲

Mitutoyo

This compact roundness measuring machine is provided with numerous user-friendly features aimed at prioritizing usability, such as a wider range for the detector, an easy-to-understand operation panel with large LCD, a D.A.T. function that powerfully supports centering and leveling adjustments, and so on.

Operating panel that is read at a glance

Supports 16 languages

Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Dutch

Analysis type


Selection buttons provide access to a wide variety of analysis types

Switching screen modes

Switch the display at the touch of a button, providing access to the [Calibration], [Centering and Leveling], [Measurement], and [Result] screens.

Zero-setting button

No fine adjustment necessary for setting the measurement position



Simple setup

Apply the current measurement setup in one go
Simple operation helps prevent operational errors

Log dial


Make detailed changes to setup and other operations

Simplified communication program for ROUNDTEST RA-120

The Roundtest RA-120 has a USB interface, enabling data to be transferred to a spreadsheet or other software.

Notch processing

Unwanted data, such as that produced by notches or scratches, can be excluded from the analysis if desired. Select between [Automatic setting] and [Arbitrary setting].



File save


Save and access [Measurement files] and [Result files] in USB memory. Data can also be totaled using the data output function with commercial tabulation software.

[Measurement file] [Measurement data (Data output)]
[Result file] [Result data (Data output)]

High-grade thermal printer

Print measurement conditions, computation results, result graphs, comments, etc., to the thermal printer. Change development graphs and output items as desired.


Sample prints



Recording paper set (optional set of 10 rolls)


Roundtest RA-120P

- Best-in-class rotational accuracy in the Compact Type Roundness Measuring Instruments
- Fine adjustment on both X- and Z-axes
- Multiple analyses through simple operation
- D.A.T. function
*except for centering/leveling device: Analog head type
- Scaled Z-axis
- Continuous ID and OD measurement
- Display function for various graphs
- High-precision air bearing
- Wide-range detector
- Supports 15 languages



Windows graphical interface


By using a mouse and buttons, identified by corresponding icons, to control the machine, the Roundtest RA-120P's interface provides excellent usability. Functions such as recalculation and graph reading are handled swiftly with easy-to-understand operations.



▲ Main screen



▲ Measurement setup screen




▲ Result screen



▲ Measurement in progress screen


This entry-level desktop tester incorporates the ROUNDPAK multi-analysis evaluation program, which provides it with analytical power close to that of more elaborate models. This is, therefore, a highly functional multi-analysis roundness measuring machine that is suitable for use not only in measurement rooms, but also in research and development sections.

Measurement screen makes ample use of graphs




Multi-analysis function

Complete with a wide range of functions including partial enlargement, auxiliary line setup, color change, displacement/angular difference of data between two points, and so on. Also equipped with notch processing and graph reading functions, which make the machine useful in research departments. Recalculation can also be performed with the filter and evaluation method changed.




Simplified layout function

Computation results for multiple items can be laid out in multiple forms on a single sheet and printed. This function also supports output to a color printer (optional).



■ Layout setting screen





■ Sample print outputs

Functions that implement greater efficiency of measurement and range of analysis types


D.A.T. function *except for centering/leveling device (analog micrometer heads)

This instrument uses the D.A.T. (Digital Adjustment Table) function available on more sophisticated models, and this provides powerful support for centering and leveling operations. To perform such operations, the user need only adjust the digital micrometer heads attached to the rotary table by the amounts indicated by the display. This function also supports measurement of notched workpieces.



Continuous ID and OD measuring function

This function comes in very handy when outside diameter and inside diameter surfaces need to be measured repeatedly, for example, with respect to coaxiality, deviation in wall thickness, etc. The inner surface can be measured and evaluated with the detector, maintaining the same measuring position for the outside diameter without changing its orientation, as illustrated on the right. Inside diameters down to 50mm can be measured.




Z-axis scale

This scale is useful when the measuring height position needs to be entered, such as when measuring coaxiality, etc. The machine uses an ABS Digimatic scale unit to provide an effective means for repetitive measurement and position setting.



IN/OUT switchable wide-range detector

The range of this detector has been extended from that of a conventional lever head by as much as four times, and is now wider than ever before. The detector can provide sufficient margin for centering and leveling jobs, or when measuring large differences. Moreover, the measuring direction can be switched between inside and outside diameters with a single touch of a button.



Types of Analysis

Type of Analysis	Measurement mode	Evaluation diagram	RA-120	RA-120P
Roundness			<input type="radio"/>	<input type="radio"/>
Flatness			<input type="radio"/>	<input type="radio"/>
Squareness	Relative to Axis 		<input type="radio"/>	<input type="radio"/>
	Relative to Plane 		<input type="radio"/>	<input type="radio"/>
Concentricity			<input type="radio"/>	<input type="radio"/>
Coaxiality	Of section 		<input type="radio"/>	<input type="radio"/>
	Of axis 		<input type="radio"/>	<input type="radio"/>

Type of Analysis	Measurement mode	Evaluation diagram	RA-120	RA-120P
Parallelism			<input type="radio"/>	<input type="radio"/>
Thickness variation	Radial 		<input type="radio"/>	<input type="radio"/>
	Axial 		<input type="radio"/>	<input type="radio"/>
Circular run-out	Radial 		<input type="radio"/>	<input type="radio"/>
	Axial 		<input type="radio"/>	<input type="radio"/>
Power spectrum			<input type="radio"/>	<input type="radio"/>
Profile operation			<input type="radio"/>	<input type="radio"/>

Optional Accessories

Interchangeable Styli

Unit: mm

12AAL021 Standard stylus *Standard accessory (stylus tip: $\phi 1.6$ carbide ball)	12AAL022 Stylus for notched workpieces (stylus tip: $\phi 3$ carbide ball)	12AAL023 Stylus for grooves (stylus tip: R0.25 sapphire)	12AAL024 Stylus for corners (stylus tip: R0.25 sapphire)
12AAL029 Stylus for extra small holes (stylus tip: $\phi 0.5$ carbide ball)	12AAL026 Stylus for small holes (stylus tip: $\phi 0.8$ carbide ball)	12AAL030 Stylus for small and deep holes (stylus tip: $\phi 1.6$ carbide ball)	12AAL028 Stylus for small and deep holes (stylus tip: $\phi 1.6$ carbide ball, L=40)
12AAL027 Stylus for small holes (stylus tip: $\phi 1$ carbide ball)	12AAL032 Cranked stylus (stylus tip: $\phi 0.5$ carbide ball)	12AAL033 Cranked stylus (stylus tip: $\phi 1$ carbide ball)	12AAL034 Stylus for flat surface
12AAL025 Stylus for filtering asperities (machining marks)	12AAL031 Disk stylus	12AAL043 M2 tapped shank for CMM styli	12AAL044 M2 tapped shank for CMM styli

* portion shows stylus except for the cranked stylus and stylus for flat surface.

* () dimension shows a distance from the tip end of stylus or the center of tip ball to the connecting surface of detector.

* Customized special interchangeable styli are available on request. Please contact any Mitutoyo office for more information.

■ Centering chuck (knurled ring operated)

Provides good operability when measuring a small-diameter workpiece. The knurled ring allows the workpiece to be clamped easily.



Order No.	211-032
Holding range	OD with internal jaws 1–36 mm ID with internal jaws 16–69 mm OD with internal jaws 25–79 mm
External size (D x H)	ø118 x 41 mm
Mass	1.2 kg

■ Collet chuck

Provides high clamping repeatability due to the use of optional precision collets. (See table at right.)



Order No.	211-051
Part holding range	ø0.5–10 mm ^{*2}
Centering error	Within 50 µm ^{*3}
Mass	1.4 kg

^{*2}: Collets to match the workpiece size range are required for use with this chuck.

^{*3}: When measured with ø5 mm pin gauge at measuring height of 30 mm.

■ X-axis stop

Allows the user to return the detector rapidly and easily to a fixed position in the X axis.



Order No.	12AAH320
Mass	65 g

■ Three-jaw chuck (key operated)

Useful where it is necessary to apply a higher clamping force to the workpiece than can be applied with the centering chuck.



Order No.	211-014
Holding range	OD with internal jaws 2–26 mm ID with internal jaws 25–68 mm OD with internal jaws 35–78 mm
External size (D x H)	ø157 x 70.6 mm
Mass	3.8 kg

■ Individual collets^{*4}

These collets are for use with the collet chuck shown at left and are acquired to match the workpiece diameter range required.

Order No.	Part Holding Range
12AAH402	ø0.5–1.0 mm
12AAH403	ø1.0–1.5 mm
12AAH404	ø1.5–2.0 mm
12AAH405	ø2.0–2.5 mm
12AAH406	ø2.5–3.0 mm
12AAH407	ø3.0–3.5 mm
12AAH408	ø3.5–4.0 mm
12AAH409	ø4.0–5.0 mm
12AAH410	ø5.0–6.0 mm
12AAH411	ø6.0–7.0 mm
12AAH412	ø7.0–8.0 mm
12AAH413	ø8.0–9.0 mm
12AAH414	ø9.0–10.0 mm

^{*4}: A collet cannot be mounted on the rotary table without a collet chuck.

^{*4}: YCC10-** Class AA, made by Yukiwa Seiko Inc. or its equivalent.

■ Vibration-damping stand



Order No.	211-013
Vibration damping system	Diaphragm type air spring
External size	615 x 515 x 51 mm
Max. loading mass	150 kg

■ Microchuck

For clamping a small workpiece, 1 mm or less in diameter, that cannot be held in the centering chuck.



Order No.	211-031
Holding range	OD: up to 1.5 mm
External size (D x H)	ø118 x 48.5 mm
Mass	0.6 kg

■ Auxiliary stage for a short workpiece

Order No. 356038



■ Reference hemisphere

Order No. 211-016



■ Magnification checking gage

Order No. 211-045



■ Gage block set for calibration

Order No. 997090




■ Replacement elements for the air filter

Order No. 358592 (for filter)
358593 (filter regulator)

■ Simplified communication program for ROUNDTTEST RA-120

The Roundtest RA-120 has a USB interface, enabling data to be transferred to a spreadsheet or other software. We also provide a program that lets you create inspection record tables using a Microsoft Excel[®] macro.



Required environment:

- OS: Windows XP-SP3
Windows 7
- Spreadsheet software: Microsoft Excel 2010

^{*}Windows OS and Microsoft Excel are products of Microsoft Corporation.

The optional USB cable is also required.

- USB cable for RA-120 series
Order No. 12AAH490


Specifications

Main unit


Model			RA-120			RA-120P				
			Dedicated electronic analysis type			Data analysis by PC				
Turntable	Rotational accuracy	Radial	(0.04+6H/10000)μm H: Probing height (mm) JISB7451-1997							
		Axial	(0.04+6X/10000)μm X: Probing radius (mm)							
	Rotational speed		6rpm							
	Effective table diameter		150mm							
	Centering range adjustment		±3mm							
	Leveling range adjustment		±1°							
	Centering/leveling device (micrometer head)		Analog head	Digital head (mm)	Digital head (inch/mm)	Analog head	Digital head (mm)	Digital head (inch/mm)		
	Maximum probing diameter		280mm (380mm in a reverse and vertical detector position)							
	Maximum workpiece diameter		440mm							
	Maximum turntable loading		25kg							
Vertical column (Z axis)	Vertical travel		280mm from the turntable top							
	Maximum probing height		280mm from the turntable top (480mm in the reverse and vertical detector configuration)							
	Maximum probing depth		100mm (minimum ID: 30mm)							
Horizontal arm (X axis)	Horizontal travel		165mm (Including a protrusion of 25mm from the turntable rotation center)							
Detector	Measuring direction		Two directional (IN/OUT switchable)							
	Measuring range		±1000μm							
	Measuring force		70 to 100mN (±30%)							
	Standard stylus (12AAL021)		Carbide ball, ø1.6mm (.06")							
Electronic unit	Measuring range		8 steps: ±(1000, 500, 200, 100, 50, 20, 10, 5)μm							
	Magnification		X5 to X200,000				X1 to X500,000			
	Filter type		Phase corrected: Gaussian, 2CRPC75, 2CRPC50				Not phase corrected: 2CR75, 2CR50 Filter OFF			
	Cutoff value		15upr, 50upr, 150upr, 500upr 15-150upr, 15-500upr, 50-500upr				15upr, 50upr, 150upr, 500upr, Manual 15-150upr, 15-500upr, 50-500upr, Manual			
	Number of measuring sections		Maximum 5				Maximum 100			
	Evaluation type		Roundness, coaxiality, concentricity, flatness, circular run-out (radial/axial), squareness (relative to axis/plane), thickness deviation, parallelism							
	Reference circle for evaluation		LSCI, MZCI, MICI, MCCI							
	Adjusting centering/leveling		DAT function (circular/multi-point switchable)							
	Functions		Notched measurement, re-calculation, limaçon error correction, continous ID and OD measurement				Notched measurement, re-calculation, limaçon error correction, remarkable point analysis (gear), harmonic analysis, continous ID and OD measurement			
	Printer		Thermal line printer, optional external printer				Windows compatible ink-jet printer			
	Display languages		Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian Turkish, Swedish, Dutch				Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian Turkish, Swedish			
	Data output	USB stick memory		Calculation result, measurement data						
		RS-232C		Calculation result, measurement data						
		SPC		Calculation result						
Others	Power supply		AC 100 – 240V							
	Power consumption		32 – 36W				21 – 24W (excluding PC system)			
	Air pressure		0.39MPa							
	Air consumption		30L/min (minimum)							
	Mass		Main unit: 32kg Air filter: 2kg							

Dimensions


External dimensions



Turntable top view



Installation floor plan





Export permission by the Japanese government may be required for exporting our products according to the Foreign Exchange and Foreign Trade Law. Please consult our sales office near you before you export our products or you offer technical information to a nonresident.

Coordinate Measuring Machines

Vision Measuring Systems

Form Measurement

Optical Measuring

Sensor Systems

Test Equipment and
Seismometers

Digital Scale and DRO Systems

Small Tool Instruments and
Data Management

Specifications are subject to change without notice.

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this pamphlet, as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs, dimensions and weights. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. Only quotations submitted by ourselves may be regarded as definitive.

Mitutoyo Corporation

20-1, Sakado 1-Chome,
Takatsu-ku, Kawasaki-shi,
Kanagawa 213-8533, Japan
T +81 (0) 44 813-8230
F +81 (0) 44 813-8231
<http://www.mitutoyo.co.jp>

Mitutoyo